

BIS Rohrschellen nach DIN 3567 (fv)

(B 15 15)

20 - 324 mm



Vorteile und Eigenschaften

- zwei gleiche Schellenhälften
- feuerverzinkt
- Material: Stahl 1.0332

Art.Nr.	D (mm)	B (mm)	s (mm)	d1 (mm)	k (mm)	k1 (mm)	VPE 1	Gew / 1 Einh (g)
4621020	20	30	5,0	11,5	57	7	1	190.00
4621022	22	30	5,0	11,5	59	7	1	192.00
4621027	27	30	5,0	11,5	66	7	1	220.00
4621030	30	30	5,0	11,5	68	7	1	230.00
4621034	34	30	5,0	11,5	72	7	1	122.00
4621038	38	30	5,0	11,5	76	7	1	248.00
4621043	43	30	5,0	11,5	82	7	1	264.00
4621045	45	30	5,0	11,5	84	7	1	280.00
4621049	49	30	5,0	11,5	88	7	1	300.00
4621057	57	40	6,0	14,0	104	9	1	553.00
4621061	61	40	6,0	14,0	108	9	1	572.00
4621077	77	40	6,0	14,0	122	9	1	655.00
4621089	89	40	6,0	14,0	136	9	1	731.00
4621108	108	50	8,0	18,0	172	11	1	1400.00
4621115	115	50	8,0	18,0	178	11	1	1450.00
4621133	133	50	8,0	18,0	196	11	1	1680.00
4621140	140	50	8,0	18,0	204	11	1	1800.00
4621159	159	50	8,0	18,0	222	11	1	2000.00
4621169	169	50	8,0	18,0	232	11	1	2050.00
4621220	220	50	8,0	18,0	284	11	1	2600.00
4621273	273	60	8,0	23,0	348	14	1	3900.00
4621324	324	60	8,0	23,0	398	14	1	4450.00

