

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 306 (replaces version 305)

Revision: 04.06.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier** 600088
- **Trade name:** Graphite Spray E-COLL
- **Article number:** 4317784243636
- **UFI:** GEM0-9T4H-NA05-5F4D
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 - SU21 Consumer uses: Private households / general public / consumers
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture** Lubricant
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 - E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH
 - EDE Platz 1
 - D-42389 Wuppertal
 - Germany

Tel. +49 202 6096-0
e-mail: sdb@ede.de
- **Further information obtainable from:** Product safety department
- **1.4 Emergency telephone number:** Giftinformationszentrum Mainz – Tel.: +49 (6131) 19240

* SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
 - Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
 - Eye Irrit. 2 H319 Causes serious eye irritation.
 - STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02 GHS07

- **Signal word** Danger

(Contd. on page 2)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 306 (replaces version 305)

Revision: 04.06.2024

Trade name: Graphite Spray E-COLL

(Contd. of page 1)


· Hazard-determining components of labelling:acetone
propan-2-ol**· Hazard statements**H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.**· Precautionary statements**P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P280 Wear protective gloves / eye protection.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.**· Additional information:**EUH066 Repeated exposure may cause skin dryness or cracking.
Buildup of explosive mixtures possible without sufficient ventilation.**· 2.3 Other hazards****· Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

*** SECTION 3: Composition/information on ingredients****· 3.2 Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

| | | |
|---|---|--------|
| CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43-XXXX | ethanol  Flam. Liq. 2, H225 | 10-50% |
|---|---|--------|

(Contd. on page 3)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 306 (replaces version 305)

Revision: 04.06.2024

Trade name: Graphite Spray E-COLL

(Contd. of page 2)

| | | |
|--|---|--------|
| CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx 01-2119498062-37-xxxx | acetone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 EUH066 | 25-50% |
| CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx | propane ⚠ Flam. Gas 1A, H220 ⚠ Acute Tox. 1, H330 Press. Gas (Comp.), H280 | 12-25% |
| CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx | butane, pure ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280 | 12-25% |
| CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25-xxxx | propan-2-ol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 | 5-12% |

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** Can form explosive gas-air mixtures.

(Contd. on page 4)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 306 (replaces version 305)

Revision: 04.06.2024

Trade name: Graphite Spray E-COLL

(Contd. of page 3)

- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.
- **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Open and handle receptacle with care.
Use only in well ventilated areas.
- **Information about fire - and explosion protection:**



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.
Do not spray onto a naked flame or any incandescent material.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Store away from oxidising agents.
- **Further information about storage conditions:**
Keep container tightly sealed.
Protect from heat and direct sunlight.

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 306 (replaces version 305)

Revision: 04.06.2024

Trade name: Graphite Spray E-COLL

(Contd. of page 4)

- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

CAS: 67-64-1 acetoneIOELV | Long-term value: 1210 mg/m³, 500 ppm

- **DNELs**

CAS: 67-63-0 propan-2-ol

| | | |
|------------|-------------------|---------------------------------|
| Inhalative | DNEL (worker) | 500 mg/m ³ (Workers) |
| | DNEL (population) | 89 mg/m ³ (cus) |

- **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
Use suitable respiratory protective device in case of insufficient ventilation.
Self-contained respiratory protective device.

· Hand protection



Protective gloves

· Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 306 (replaces version 305)

Revision: 04.06.2024

Trade name: Graphite Spray E-COLL

(Contd. of page 5)

· Eye/face protection

Tightly sealed goggles

· Body protection: Light weight protective clothing**SECTION 9: Physical and chemical properties****· 9.1 Information on basic physical and chemical properties****· General Information**

| | |
|--|-----------------------------------|
| · Colour: | Black |
| · Odour: | Acetone-like |
| · Odour threshold: | Not determined. |
| · Melting point/freezing point: | Undetermined. |
| · Boiling point or initial boiling point and boiling range | -20 °C |
| · Flammability | Not applicable. |
| · Lower and upper explosion limit | |
| · Lower: | 1.5 Vol % |
| · Upper: | 9.5 Vol % |
| · Flash point: | -21 °C |
| · Auto-ignition temperature: | 365 °C |
| · Decomposition temperature: | Not determined. |
| · pH | Not determined. |
| · Viscosity: | |
| · Kinematic viscosity | Not determined. |
| · Kinematic: 23 °C - 4 mm (ISO 2431) | |
| · Dynamic: | Not determined. |
| · Solubility | |
| · water: | Not miscible or difficult to mix. |
| · Partition coefficient n-octanol/water (log value) | Not determined. |
| · Vapour pressure at 20 °C: | 4,200 hPa |
| · Density and/or relative density | |
| · Density at 20 °C: | 0.79 g/cm ³ |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |

· 9.2 Other information

| | |
|---|------------------------------|
| · Appearance: | |
| · Form: | Aerosol |
| · Important information on protection of health and environment, and on safety. | |
| · Ignition temperature: | Product is not selfigniting. |
| · Explosive properties: | Not determined. |
| · VOC (EC) g/l | <840.0 g/l |
| · Change in condition | |
| · Drip point: | |
| · Oxidising properties | Not determined. |

(Contd. on page 7)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 306 (replaces version 305)

Revision: 04.06.2024

Trade name: Graphite Spray E-COLL

(Contd. of page 6)

- **Evaporation rate** Not applicable.
- **Information with regard to physical hazard classes**
 - **Explosives** Void
 - **Flammable gases** Void
 - **Aerosols** Extremely flammable aerosol. Pressurised container: May burst if heated.
 - **Oxidising gases** Void
 - **Gases under pressure** Void
 - **Flammable liquids** Void
 - **Flammable solids** Void
 - **Self-reactive substances and mixtures** Void
 - **Pyrophoric liquids** Void
 - **Pyrophoric solids** Void
 - **Self-heating substances and mixtures** Void
 - **Substances and mixtures, which emit flammable gases in contact with water** Void
 - **Oxidising liquids** Void
 - **Oxidising solids** Void
 - **Organic peroxides** Void
 - **Corrosive to metals** Void
 - **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Reacts with strong acids and oxidising agents.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

*** SECTION 11: Toxicological information**

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:****CAS: 64-17-5 ethanol**

| | | |
|------|------|-------------------|
| Oral | LD50 | 7,060 mg/kg (rat) |
|------|------|-------------------|

(Contd. on page 8)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 306 (replaces version 305)

Revision: 04.06.2024

Trade name: Graphite Spray E-COLL

(Contd. of page 7)

| | | |
|-----------------------------------|---------|-----------------------------|
| Inhalative | LC50/4h | 20,000 ppm (rat) |
| CAS: 67-64-1 acetone | | |
| Oral | LD50 | 5,800 mg/kg (rat) |
| Dermal | LD50 | 20,000 mg/kg (rabbit) |
| Inhalative | LC50/4h | 76 mg/m ³ (rat) |
| CAS: 74-98-6 propane | | |
| Inhalative | LC50/4h | >20 mg/m ³ (rat) |
| CAS: 106-97-8 butane, pure | | |
| Inhalative | LC50/4h | 658 ppm (rat) |
| CAS: 67-63-0 propan-2-ol | | |
| Oral | LD50 | 5,045 mg/kg (rat) |
| Dermal | LD50 | 12,800 mg/kg (rabbit) |
| Inhalative | LC50/4h | 30 ppm (rat) |

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

CAS: 67-64-1 acetone

| | |
|------------|--|
| LC50 (96h) | 5,000 mg/L (Lepomis macrochirus) |
| LC50/48h | 8,800 mg/l (Daphnia magna) |
| NOEC | 430 mg/l (algae) |
| NOEC/16h | 1,700 mg/l (Pseudomonas putida) |
| NOEC/48h | 4,740 mg/l (Pseudokirchneriella subcapitata) |
| 96h LC50 | 5,540 mg/l (Oncorhynchus mykiss) |

(Contd. on page 9)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 306 (replaces version 305)

Revision: 04.06.2024

Trade name: Graphite Spray E-COLL

(Contd. of page 8)

CAS: 67-63-0 propan-2-ol

EC50/24h >10,000 mg/l (daphnia)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods:**
Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste.
Observe local regulations.

European waste catalogue

16 05 04* gases in pressure containers (including halons) containing hazardous substances

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** UN1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable

14.3 Transport hazard class(es)

- **ADR**



- **Class** 2.5F Gases.

(Contd. on page 10)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 306 (replaces version 305)

Revision: 04.06.2024

Trade name: Graphite Spray E-COLL

(Contd. of page 9)

· Label 2.1**· IMDG, IATA****· Class** 2.1 Gases.**· Label** 2.1**· 14.4 Packing group****· ADR, IMDG** Void**· 14.5 Environmental hazards:****· Marine pollutant:** No**· 14.6 Special precautions for user****· Hazard identification number (Kemler code):** -**· EMS Number:** F-D,S-U**· Stowage Code** SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.**· Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.**· 14.7 Maritime transport in bulk according to IMO instruments** Not applicable.**· Transport/Additional information:****· ADR****· Limited quantities (LQ)** 1L**· Excepted quantities (EQ)** Code: E0

Not permitted as Excepted Quantity

· Transport category 2**· Tunnel restriction code** D**· IMDG****· Limited quantities (LQ)** 1L**· Excepted quantities (EQ)** Code: E0

Not permitted as Excepted Quantity

· UN "Model Regulation": UN 1950 AEROSOLS, 2.1

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 306 (replaces version 305)

Revision: 04.06.2024

Trade name: Graphite Spray E-COLL

(Contd. of page 10)

SECTION 15: Regulatory information

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

· **DIRECTIVE 2004/42/CE**

Directive 2004/42/CE: Cat. 2.1e) limit value 840 g/l VOC, produkt contains < 840 g/l VOC

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard-determining components of labelling:**

acetone

propan-2-ol

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P280 Wear protective gloves / eye protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **Exposure scenario(s)**

Exposure scenario(s) of ingredients (if present) are available on request at:

sdb@ede.de

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

(Contd. on page 12)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024

Version number 306 (replaces version 305)

Revision: 04.06.2024

Trade name: Graphite Spray E-COLL

(Contd. of page 11)

H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.

· **Department issuing SDS:** Product safety department

· **Contact:** sdb@ede.de

· **Date of previous version:** 02.09.2021

· **Version number of previous version:** 305

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 1: Acute toxicity – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· * **Data compared to the previous version altered.**
