

Printing date 15.01.2024 Version number 305 (replaces version 304) Revision: 15.01.2024

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600253

· Trade name: Underbody Protection Spray E-COLL

· Article number: 4317784341684

UFI: SWYQ-64R4-DC0K-1KQ1

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Anticorrosion additive
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

· Signal word Danger



Printing date 15.01.2024 Version number 305 (replaces version 304) Revision: 15.01.2024

Trade name: Underbody Protection Spray E-COLL

(Contd. of page 1)

## · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy

xvlene

Hydrocarbons, C9-unsaturated, polymerised

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.H317 May cause an allergic skin reaction.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

#### · 2.3 Other hazards

#### · Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

### · 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	10-<25%
EC number: 927-241-2 Reg.nr.: 01-2119471843-32-XXXX	♦ Flam. Liq. 3, H226 ♠ Asp. Tox. 1, H304	
110g 01 2110 11 10 10 02 70 00 0		
	Aquatic Chronic 3, H412	
CAS: 74-98-6	propane	10-<25%
EINECS: 200-827-9 Index number: 601-003-00-5	♦ Flam. Gas 1A, H220 Acute Tox. 1, H330	
Reg.nr.: 01-2119486944-21-xxxx	Press. Gas (Comp.), H280	
<u> </u>	` ' '	d on nogo 2\

(Contd. on page 3)



Printing date 15.01.2024 Version number 305 (replaces version 304) Revision: 15.01.2024

Trade name: Underbody Protection Spray E-COLL

		ontd. of page 2)
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46-xxxx	ethyl acetate     Flam. Liq. 2, H225     Eye Irrit. 2, H319; STOT SE 3, H336     EUH066	2.5-10%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 02-2119752448216-32	xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane  Flam. Gas 1A, H220 Press. Gas (Comp.), H280	2.5-10%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene Flam. Liq. 2, H225 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H332	0.1-<1%
CAS: 71302-83-5 EC number: 615-276-3 Reg.nr.: 01-2119555292-40-XXXX	Hydrocarbons, C9-unsaturated, polymerised  Skin Sens. 1A, H317 Aquatic Chronic 3, H412	0.1-<1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

## · 4.1 Description of first aid measures

## · General information:

Personal protection for the First Aider. Immediately remove any clothing soiled by the product.

## · After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

## · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

## · After swallowing:

Rinse out mouth and then drink plenty of water.

Seek immediate medical advice.

#### · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 4)



Printing date 15.01.2024 Version number 305 (replaces version 304) Revision: 15.01.2024

Trade name: Underbody Protection Spray E-COLL

(Contd. of page 3)

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
   CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 302, powder of water spray. Figure larger lines with water spray of algorithment
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- 5.3 Advice for firefighters
- **Protective equipment:** Wear self-contained respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

## **SECTION 6: Accidental release measures**

 $\cdot$  6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Dispose contaminated material as waste according to section 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Open and handle receptacle with care. Use only in well ventilated areas.

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.



Printing date 15.01.2024 Version number 305 (replaces version 304) Revision: 15.01.2024

Trade name: Underbody Protection Spray E-COLL

(Contd. of page 4)

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

· 8.1 Control parameters

Ingradianta wit	h limit valua	that require	manitaring	at the workplace:
· inarealents wit	n iimit vaiues	tnat reduire	monitorina	at the workblace:

CAS: 141-78-6 ethyl acetate

IOELV Short-term value: 1468 mg/m³, 400 ppm

Long-term value: 734 mg/m³, 200 ppm

CAS: 1330-20-7 xylene

IOELV Short-term value: 442 mg/m³, 100 ppm

Long-term value: 221 mg/m³, 50 ppm

Skin

CAS: 100-41-4 ethylbenzene

IOELV Short-term value: 884 mg/m³, 200 ppm

Long-term value: 442 mg/m<sup>3</sup>, 100 ppm

Skin

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Short term filter device:

Filter A/P2



Printing date 15.01.2024 Version number 305 (replaces version 304) Revision: 15.01.2024

Trade name: Underbody Protection Spray E-COLL

(Contd. of page 5)

## · Hand protection



## · Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

## · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

## · Eye/face protection



Tightly sealed goggles

· Body protection: Protective work clothing

## **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Black

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range Not applicable, as aerosol.

· Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.Upper: Not determined.

· Flash point: Not applicable, as aerosol.

· Auto-ignition temperature: 324 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

· Kinematic: 23 °C - 4 mm (ISO 2431)

· **Dynamic:** Not determined.

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure: Not determined.

· Density and/or relative density

Density at 20 °C:
 Relative density
 O.9 g/cm<sup>3</sup>
 Not determined.

(Contd. on page 7)



Printing date 15.01.2024 Version number 305 (replaces version 304) Revision: 15.01.2024

Not determined.

Trade name: Underbody Protection Spray E-COLL

(Contd. of page 6)

· 9.2 Other information

· Vapour density

· Appearance:

· Form: Aerosol

Important information on protection of health

and environment, and on safety.

• **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Not determined.

· Solvent separation test:

· Organic solvents: 56.85 %

· Change in condition

· Drip point:

Oxidising propertiesEvaporation rateNot determined.Not applicable.

· Information with regard to physical hazard

classes

ExplosivesFlammable gasesVoid

· Aerosols Extremely flammable aerosol, Pressurised container:

May burst if heated.

Oxidising gases
Void
Gases under pressure
Void
Flammable liquids
Flammable solids
Self-reactive substances and mixtures
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Void

Self-heating substances and mixtures
 Substances and mixtures, which emit flammable gases in contact with water
 Oxidising liquids
 Oxidising solids
 Organic peroxides
 Corrosive to metals
 Desensitised explosives

**SECTION 10: Stability and reactivity** 

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 8)



Printing date 15.01.2024 Version number 305 (replaces version 304) Revision: 15.01.2024

Trade name: Underbody Protection Spray E-COLL

(Contd. of page 7)

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	>15,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rab)
Inhalative	LC50/4h	76 ppm (rat)
CAS: 74-9	CAS: 74-98-6 propane	
Inhalative	LC50/4h	>20 mg/m³ (rat)
CAS: 141-78-6 ethyl acetate		
Oral	LD50	5,620 mg/kg (rabbit)
Inhalative	LC50/4h	1,600 ppm (rat)
CAS: 1330-20-7 xylene		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
CAS: 100-41-4 ethylbenzene		
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

(Contd. on page 9)



Printing date 15.01.2024 Version number 305 (replaces version 304) Revision: 15.01.2024

Trade name: Underbody Protection Spray E-COLL

(Contd. of page 8)

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity:

CAS: 75-28-5 isobutane

EC50 (48h) 69.43 mg/L (daphnia)

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

#### **SECTION 13: Disposal considerations**

## · 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

## · European waste catalogue

15 01 10\* packaging containing residues of or contaminated by hazardous substances

16 05 04\* gases in pressure containers (including halons) containing hazardous substances

## **SECTION 14: Transport information**

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA

UN1950



Printing date 15.01.2024 Version number 305 (replaces version 304) Revision: 15.01.2024

Trade name: Underbody Protection Spray E-COLL

(Contd. of page 9)

· 14.2 UN proper shipping name

· ADR UN1950 AEROSOLS

· IMDG AEROSOLS

· IATA AEROSOLS, solution

· 14.3 Transport hazard class(es)

· ADR



· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



· Class 2 Gases.

· Label 2.1

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Gases.

• EMS Number: F-D,S-U

· 14.7 Maritime transport in bulk according to IMO

**instruments** Not applicable.

Transport/Additional information:

· ADR

· Limited quantities (LQ) 1L

• Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

Transport categoryTunnel restriction code

· UN "Model Regulation": UN1950, AEROSOLS, 2.1

## **SECTION 15: Regulatory information**

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 11)



Printing date 15.01.2024 Version number 305 (replaces version 304) Revision: 15.01.2024

Trade name: Underbody Protection Spray E-COLL

(Contd. of page 10)

## · Hazard pictograms





· Signal word Danger

## · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy

xylene

Hydrocarbons, C9-unsaturated, polymerised

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Causes serious eye irritation. H319 May cause an allergic skin reaction. H317

#### · Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use. P251

Avoid breathing dust/fume/gas/mist/vapours/spray. P261 Wear protective gloves / eye protection / face protection. P280

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

## · Directive 2012/18/EU

- Named dangerous substances ANNEX I Methanol
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

## · National regulations:

#### · Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

## Exposure scenario(s)

Exposure scenario(s) of ingredients (if present) are available on request at:

(Contd. on page 12)



Printing date 15.01.2024 Version number 305 (replaces version 304) Revision: 15.01.2024

Trade name: Underbody Protection Spray E-COLL

(Contd. of page 11)

sdb@ede.de

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## · Relevant phrases

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking.

· Contact: sdb@ede.de

H373

 Date of previous version: 20.11.2023 · Version number of previous version: 304

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 1: Acute toxicity – Category 1

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

## · \* Data compared to the previous version altered.