

Printing date 26.09.2023 Version number 306 Revision: 26.09.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600167

· Trade name: Contact Spray E-COLL

· Article number: 4317784179638

· UFI: Q1ER-SXSH-NC0F-42GQ

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Penetrating oil
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS09

· Signal word Danger



Printing date 26.09.2023 Version number 306 Revision: 26.09.2023

Trade name: Contact Spray E-COLL

(Contd. of page 1)

· Hazard-determining components of labelling:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Distillates (petroleum), hydrotreated light naphthenic

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

ially statements
If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Avoid breathing mist/vapours/spray.
Use only outdoors or in a well-ventilated area.
Collect spillage.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Dispose of contents/container in accordance with local/regional/national/international

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

regulations.

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:					
CAS: 64742-47-8 EINECS: 265-149-8 Index number: 649-422-00-2 Reg.nr.: 01-2119456620-43	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Asp. Tox. 1, H304 EUH066	50-100%			
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane, pure Flam. Gas 1A, H220 Press. Gas (Comp.), H280	2.5-<25%			
CAS: 64742-53-6 EINECS: 265-156-6 Index number: 649-466-00-2 Reg.nr.: 01-2119480375-34-xxxx	Distillates (petroleum), hydrotreated light naphthenic Asp. Tox. 1, H304	2.5-10%			
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	0-10%			



Printing date 26.09.2023 Version number 306 Revision: 26.09.2023

Trade name: Contact Spray E-COLL

	(Co	ntd. of page 2)
CAS: 124-38-9	carbon dioxide	0-<2.5%
EINECS: 204-696-9	Press. Gas (Comp.), H280	
CAS: 95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	0-<1%
EINECS: 204-414-9	♦ STOT RE 2, H373	
	🔖 Skin Corr. 1C, H314	
	Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410	
	(M=10)	
	Acute Tox. 4, H302; Acute Tox. 4, H312	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Personal protection for the First Aider. Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.

(Contd. on page 4)



Printing date 26.09.2023 Version number 306 Revision: 26.09.2023

Trade name: Contact Spray E-COLL

(Contd. of page 3)

- 5.3 Advice for firefighters
- · Protective equipment: Do not inhale explosion gases or combustion gases.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

- · 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Open and handle receptacle with care. Use only in well ventilated areas.

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Keep container tightly sealed.

(Contd. on page 5)



Printing date 26.09.2023 Version number 306 Revision: 26.09.2023

Trade name: Contact Spray E-COLL

(Contd. of page 4)

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

CAS: 124-38-9 carbon dioxide

IOELV Long-term value: 9000 mg/m³, 5000 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation. Short term filter device:

Filter A/P2

· Hand protection



Protective gloves

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Safety glasses
- · Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Colour:

Yellow-brown

· Odour: Characteristic



Printing date 26.09.2023 Version number 306 Revision: 26.09.2023

-0.5 °C (CAS: 106-97-8 butane, pure)

Not applicable.

Trade name: Contact Spray E-COLL

(Contd. of page 5)

· Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range

· Flammability

· Lower and upper explosion limit

1.5 Vol % · Lower: · Upper: 8.5 Vol %

-60 °C (CAS: 106-97-8 butane, pure) · Flash point: · Auto-ignition temperature: 365 °C (CAS: 106-97-8 butane, pure)

· Decomposition temperature: Not determined. · pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

Kinematic: 23 °C - 4 mm (ISO 2431)

· Dynamic: Not determined.

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C: 2,800 hPa (CAS: 106-97-8 butane, pure)

Density and/or relative density

· Density at 20 °C: 0.76 g/cm³ · Relative density Not determined. Not determined. · Vapour density

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and environment, and on safety.

· Ignition temperature: Product is not selfigniting.

· Explosive properties: Not determined.

Change in condition

· Drip point:

· Oxidising properties Not determined. · Evaporation rate Not applicable.

· Information with regard to physical hazard

classes

· Explosives Void · Flammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised container:

May burst if heated.

Void · Oxidising gases · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable

gases in contact with water Void · Oxidising liquids Void

(Contd. on page 7)



Printing date 26.09.2023 Version number 306 Revision: 26.09.2023

Trade name: Contact Spray E-COLL

Contd. of page 6)

Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives

(Contd. of page 6)

Void

Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
 No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:					
CAS: 106-	CAS: 106-97-8 butane, pure				
Inhalative	LC50/4h	658 ppm (rat)			
CAS: 64742-53-6 Distillates (petroleum), hydrotreated light naphthenic					
Oral	LD50	5,000 mg/kg (rat)			
Dermal	LD50	5,000 mg/kg (rat)			
CAS: 74-98-6 propane					
Inhalative	LC50/4h	>20 mg/m³ (rat)			
CAS: 95-38-5 2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol					
Oral	LD50	1,256 mg/kg (rat)			
Dermal	LD50	2,000 mg/kg (rabbit)			

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.

(Contd. on page 8)



Printing date 26.09.2023 Version number 306 Revision: 26.09.2023

Trade name: Contact Spray E-COLL

(Contd. of page 7)

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:					
CAS: 64742-53-6 Distillates (petroleum), hydrotreated light naphthenic					
EC50 (21d)	>10 mg/L (Daphnia galeata)				
EC50 (48h)	>10,000 mg/L (Daphnia galeata)				
NOEC (21d)	10 mg/l (Daphnia galeata)				
CAS: 95-38-5 2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol					
LC50 (96h)	0.3 mg/L (Brachydanio rerio)				
EC50/72h	0.03 mg/l (Desmodesmus subspicatus)				
EL50/48h	0.136 mg/l (Daphnia galeata)				

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.



Printing date 26.09.2023 Version number 306 Revision: 26.09.2023

Trade name: Contact Spray E-COLL

(Contd. of page 8)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European waste catalogue

16 05 04* gases in pressure containers (including halons) containing hazardous substances

15 01 10* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR UN1950 AEROSOLS

· IMDG, IATA AEROSOLS

· 14.3 Transport hazard class(es)

· ADR





· Class 2 5F Gases.

· Label 2.1

· IMDG





Class
 Label
 2 Gases.
 2.1

·IATA



· Class 2 Gases. · Label 2.1

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

Symbol (fish and tree)

(Contd. on page 10)



Printing date 26.09.2023 Version number 306 Revision: 26.09.2023

Trade name: Contact Spray E-COLL

(Contd. of page 9)

· Special marking (ADR): Symbol (fish and tree)

• 14.6 Special precautions for user Warning: Gases.

• EMS Number: F-D,S-U

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)
 Transport category
 Tunnel restriction code

· UN "Model Regulation": UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS09

· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Distillates (petroleum), hydrotreated light naphthenic

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use. P261 Avoid breathing mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P391 Collect spillage.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I Methanol



Printing date 26.09.2023 Version number 306 Revision: 26.09.2023

Trade name: Contact Spray E-COLL

(Contd. of page 10)

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220	Extremely flammable	gas.

Contains gas under pressure; may explode if heated. H280

Harmful if swallowed. H302

May be fatal if swallowed and enters airways. H304

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects. H410

EUH066 Repeated exposure may cause skin dryness or cracking.

Department issuing SDS: Product safety department

· Contact: sdb@ede.de

· Date of previous version: 26.09.2023

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1C: Skin corrosion/irritation – Category 1C STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

· * Data compared to the previous version altered.